

Comparison:

FX6 vs. Filtrax

Robust and lightweight filtration options

NEW



Feature	FX6	Filtrax sc
Directly connected filtration module Easy installation with less mounting hardware needed, thanks to the integrated sample pump and compressor for the filtration module.	✓	✗
Increased compressor lifetime Save money with an extended compressor lifetime, as the compressor only runs when needed and reduces replacement frequency by 50% to every 4 years.	✓ (FX620 only)	✗
Rotating filter module holder The rotation of the filter module holder optimises the flow shear of the filter module surface, increasing its cleaning effectiveness and reducing resistance during removal.	✓	✗
Lightweight filter module Ensure easy maintenance and enhanced employee safety with a lightweight filter module featuring only one membrane to clean.	✓ (2.2 - 3.5 kg)	✗ (9 kg)
User maintenance made easy Less time needed for user maintenance with a membrane that needs cleaning only every 3 months and an air supply tube with a larger diameter that increases cleaning capacity by 33% and only needs replacing every 6 months.	✓ (typically every 3 months)	✓ (typically every month)
Easy filter module replacement Optimised design of the filter module features a click installation and release button, introducing a quick-release system for improved filter module replacement.	✓	✗
Service protected A complete portfolio of field service plans to help you protect your investment and peace of mind.	✓	✓



Technical specifications		
Dimensions (H x W x D)	FX610: 287 x 348 x 81 mm FX620: 408 x 424 x 86 mm	92 x 500 x 340 mm
Weight	2.2 kg - 3.5 kg	9 kg
Pump for filtration module	Integrated	External
Maintenance schedule		
Annual Maintenance Set	x	12 months
Filter module	12 months	12 months
Compressor	48 months	24 months
Sample Pump head	24 months	x

HYXO
Part of WEST Invest Group

Sortilantie 5 A, PL 16
04261 KERAVALA
puh. 010 417 4500
hyxo@hyxo.fi
www.hyxo.fi

